



**8.0 Megapixel CCD** The high-resolution CCD, 3x optical, 15x total zoom capability helps you capture subtle detail up close, or at a distance.

**2.5" HyperCrystal™ LCD** This large super clear LCD helps you view and share images from angles up to 160 degrees – during shooting and playback, even in bright sunlight.

**All-Weather Construction** Engineered and perfected in the great outdoors, its tightly sealed metal body will serve its purpose at the beach or in a downpour.

**Built-in Help GUIDE** A brief in-camera description helps you choose the ideal setting for each situation and purpose.


**24 Selectable Shooting Modes** Take control in any shooting situation – in manual modes or automatically, including landscapes, portrait, indoor, night scene and more.



**TruePic TURBO™ Image Processor** This exclusive Olympus technology enables smoother, more accurate images with accelerated startup and shutter release times.

**QuickTime® Movie Mode with Audio** Bring your pictures to life, then e-mail them to family and friends.

**Bright Capture Technology** In low lighting, this new Olympus technology allows you to preview subjects more clearly and capture a brighter image in specific scene modes. Engage this smart technology and improve your experience by extending your flash distance, reducing image blur and boosting the high speed sequential shooting function.



This stylish performer offers extreme functionality. With an 8.0 megapixel CCD and 15x total zoom capability, Stylus 800 provides extraordinarily high resolution – helping you get real close, then blow up your images with eye-popping results. To share your shots, the super clear 2.5" HyperCrystal LCD offers fine detail and vibrant color from any angle, even in direct sunlight. Shooting in low light? Thanks to our Bright Capture Technology, you can see your picture clearly on the LCD and capture your image with outstanding quality. Use 24 selectable shooting modes including manual exposure controls. PictBridge™ enables direct printing, no computer necessary. All-weather. All new. All in the most exciting Stylus ever.



## Olympus® Stylus® 800 Specifications

Stock No. 225625

<b>Imager:</b>	8.0 megapixel effective, 8.3 megapixel gross, 1/1.8" (1.41cm) CCD
<b>Lens:</b>	8.0 – 24.0mm (38 – 114mm equivalent in 35mm photography), 6 lenses in 5 groups, 3 aspherical lenses
<b>Zoom:</b>	Seamless to 15x (3x optical and 5x digital combined)
<b>Aperture Range:</b>	f2.8/f4.9 (adjustable in 1/3 EV steps)
<b>LCD:</b>	2.5" (6.35cm) HyperCrystal™ LCD, approx. 215,000 pixel
<b>Focus System:</b>	CCD Contrast detection
<b>Focus Range:</b>	Normal mode: 19.7" – infinity (0.5m – infinity) Macro mode W: 7.9" – 19.7" (0.2m – 0.5m), T: 11.8" – 19.7" (0.3m – 0.5m) Super Macro Mode: 1.2" – 19.7" (3cm – 50cm)
<b>Focus Mode:</b>	iESP auto, Spot AF
<b>Shutter Speed:</b>	1/2000 sec – 1/2 sec. (up to 4 sec. in Night Scene mode)
<b>ISO:</b>	Auto, 64, 100, 200, 400, 800 (SQ1), 1600 (SQ1) (equivalent)
<b>Metering Mode:</b>	Digital ESP multi-pattern, Spot metering
<b>White Balance:</b>	iESP multi-pattern auto TTL, Pre-set (Daylight, Overcast, Tungsten, and Fluorescent1, Fluorescent2, Fluorescent3)
<b>Exposure Compensation:</b>	±2 EV steps in 1/3 EV steps
<b>Recording Modes:</b>	DCF Exif 2.2, JPEG, PIM 3
<b>Adjustment Resolutions:</b>	3264 x 2448 (SHQ) 3264 x 2448 (HQ) 2560 x 1920 (SQ1) 2272 x 1704 (SQ1) 2048 x 1536 (SQ1) 1600 x 1200 (SQ2) 1280 x 960 (SQ2) 1024 x 768 (SQ2) 640 x 480 (SQ2)
<b>Shooting Modes:</b>	24 shooting modes; P, A, S, Scene Preset (Landscape, Landscape + Portrait, Portrait, Indoor, Sport, Beach & Snow, Behind Glass, Self-Portrait + Self-Timer, Self-Portrait, Sunset, Night Scene, Night + Portrait, Night Shoot, Cuisine, Documents, Candle, Fireworks, Shoot & Select1, Shoot & Select2), Image Blur Reduction, Movie
<b>Panorama:</b>	Up to 10 frames automatically stitchable with Olympus Master software when using Olympus brand xD-Picture Card™
<b>Sequential Shooting:</b>	Normal: 1.3 frames per second, 4 frames or more in HQ mode High Speed: 4 frames per second, 10 frames or more in SQ1 mode
<b>Shooting Assist Functions:</b>	Histogram

## Available Accessories

Product Number	UPC	Accessory
200400	050332-297029	Leather Case
200496	298538	Metal Neck Strap
200840	139084	16MB xD-Picture Card™
200841	139091	32MB xD-Picture Card™
200842	139107	64MB xD-Picture Card™
200843	139114	128MB xD-Picture Card™
200844	139565	256MB xD-Picture Card™
200859	142558	512MB xD-Picture Card™
200495	155046	1GB xD-Picture Card™
200830	139138	MAUSB-10 xD-Picture Card/SmartMedia™ USB Reader/Writer
200891	144422	MAUSB-100 xD-Picture Card™ USB Reader/Writer
200335	153738	MAUSB-300 xD-Picture Card™ USB Reader/Writer
200837	139512	MACF-10 xD-Picture Card™ /Compact Flash Adapter
200835	139145	MAPC-10 xD-Picture Card/SmartMedia™ PCMCIA/PC Card Adapter
200845	296473	xD-Picture Card™ Media Wallet
200838	139411	Li-12B Replacement Battery
200846	139428	Li-10C Replacement Charger
200850	296688	D-7AC AC Adapter
200372	152625	CB-USB6 Digital Camera USB Cable (replacement)
200347	152632	CB-AVC3 Digital Camera A/V Cable (replacement)
200893	297883	2-Year Extended Digital Warranty
200493	298507	Stylus Digital Accessory Kit Includes Case, Battery and Metal Neck Strap

## Package Contents

Stylus 800 Camera	Basic Instruction Manual
Wrist Strap	Quick Start Guide
USB Cable	Warranty Card
Audio/Video Cable	CD ROM: Olympus Master™ Software and Advanced Manual
Li-12B Li-ion Rechargeable Battery and Charger	

<b>Movie Mode:</b>	QuickTime® Movie with Sound, SHQ: 640 x 480/15fps, HQ: 320 x 240/15fps, SQ: 160 x 120/15fps
<b>Image Processing:</b>	TruePic TURBO™ Image Processor
<b>Pixel Mapping:</b>	Automatic Pixel Mapping (APM) available via menu setting
<b>Noise Reduction:</b>	Set automatically at shutter speeds of 1 second or longer
<b>Image Playback:</b>	Still image: Single, Index display (4/9/16/25), Up to 8x enlargement, Slide-Show, Rotation, Calendar, Album, Histogram Movie: Normal, Reverse, Frame-by-frame
<b>Playback Edit Effects:</b>	Still image: Black and White, Sepia, Resize, Rotation, Red-Eye Fix Movie: Frame Index
<b>Direct Printing Options:</b>	PictBridge and DPOF
<b>Flash:</b>	Built-in
<b>Flash Modes:</b>	Auto (for low light and back-lit conditions) Red-eye Reduction Fill-in Off
<b>Flash Working Range:</b>	Program Auto: W: 21.3 ft (6.5m), T: 11.5ft (3.5m) ISO1600: W: 42.0 ft(12.8m), T: 23.6 ft (7.2m)
<b>Self-Timer:</b>	12 seconds/2 seconds by Remote Control
<b>Settings Memorization:</b>	On/Off (Hold changes/Reset to default settings)
<b>Date/Time Calendar:</b>	Simultaneous recording into image data, Automatic up to 2099
<b>Memory:</b>	32MB internal memory (21.3MB available memory)
<b>Removable Media Card:</b>	xD-Picture Card™ (16, 32, 64, 128, 256, 512MB or 1GB)
<b>Outer Connectors:</b>	USB connector & audio/video multi-terminal, DC input
<b>Auto-Connect USB:</b>	2.0 Full Speed
<b>Weatherproof:</b>	Yes
<b>System Requirements:</b>	Windows 98SE/2000 Pro/ME/XP, Mac OS 10.1 and higher
<b>Operating Environment:</b>	Operation: 32° – 104°F (0° – 40°C), 30% – 90% humidity Storage: -4° – 140°F (-20° – 60°C), 10% – 90% humidity
<b>Power Supply:</b>	Li-Ion rechargeable battery (Li-12B), AC Adapter
<b>Size:</b>	4.1" W x 2.3" H x 1.3" D (103mm x 57.5mm x 33mm)
<b>Weight:</b>	6.4 oz. (181.5g) without battery and media card

## Memory Card Storage Capacity

	Quality	Pixel Resolution	256 MB xD-Picture Card™ (Optional)	1 GB xD-Picture Card™ (Optional)
Still Image (w/o sound) Unit: shots	SHQ	3264 x 2448	63 shots	255 shots
	HQ	3264 x 2448	124 shots	499 shots
	SQ1	2560 x 1920	210 shots	841 shots
		2272 x 1704	262 shots	1048 shots
		2048 x 1536	326 shots	1305 shots
	SQ2	1600 x 1200	389 shots	1560 shots
		1280 x 960	614 shots	2460 shots
		1024 x 768	940 shots	3762 shots
		640 x 480	1453 shots	5815 shots
	Still Image (with sound) Unit: shots	SHQ	3264 x 2448	63 shots
HQ		3264 x 2448	122 shots	492 shots
SQ1		2560 x 1920	204 shots	820 shots
		2272 x 1704	253 shots	1015 shots
		2048 x 1536	313 shots	1254 shots
SQ2		1600 x 1200	371 shots	1487 shots
		1280 x 960	570 shots	2284 shots
		1024 x 768	841 shots	3366 shots
	640 x 480	1229 shots	4920 shots	
Movie (with sound) Unit: min.	SHQ	640 x 480	approx. 220 sec.	approx. 900 sec.
	HQ	320 x 240	approx. 650 sec.	approx. 2600 sec.
	SQ	160 x 120	approx. 1650 sec.	approx. 6750 sec.

All capacity figures are approximate.

OLYMPUS SCHOOL OF  
DIGITAL PHOTOGRAPHY

The Olympus School of Digital Photography is a one-day workshop covering everything from digital image capture to final output. To register, visit [www.olympusphotoschool.com](http://www.olympusphotoschool.com) or call 1-800-645-8100 x6161.



Olympus Digital Still Cameras can be used with confidence wherever you go. They are backed by a one-year repair warranty service that is available worldwide. Please contact our service center or check the Authorized Distributors list for service and applicable areas of service. May not be available in all areas.

Specifications subject to change without notice or obligation on the part of the manufacturer.

© 2005 Olympus Imaging America Inc. All rights reserved. Printed in the United States of America.

Olympus and Stylus are trademarks or registered trademarks of Olympus Corporation, Olympus Imaging America Inc. or their affiliated entities. All trademarks and registered trademarks listed herein are the property of their respective holders. D1266-0505